

# ACumist<sup>®</sup> 3415G

---

Micronized PTFE Modified Polyethylene Homopolymer for use in both solvent and water borne coatings provides slip, scratch & abrasion resistance, anti-blocking and aids in metal fabrication for rigid packaging, coil coated metals, wood coatings, powder coatings, inks and other coatings which require for surface protection.

PFOA, PFOS, PFCA are EU REACH compliance

\* ACumist<sup>®</sup> 3415G does not intentionally incorporate PFOA, PFOS, PFCA into the product either as raw materials, processing aids or additives. Honeywell has conducted sound analytical tests with results as not being detected.

## TYPICAL PROPERTIES

Property	Value
Hardness	<0.5
Drop Point, Mettler	126°C (259°F)
Density	1.10
Acid Number	Nil

## PRODUCT FORM AND SIZE

Property	Value
Product Form	Micronized powder
Size	4.0 to 5.5

DISCLAIMER: Although all statements and information contained herein are believed to be accurate and reliable, they are presented without guarantee or warranty of any kind, express or implied. Information provided herein does not relieve the user from the responsibility of carrying out its own tests and experiments, and the user assumes all risks and liability for use of the information and results obtained. Statements or suggestions concerning the use of materials and processes are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all toxicity data and safety measures are indicated herein or that other measures may not be required.

© 2022 Honeywell International Inc.

All rights reserved

